



## ENFM part number for Bimetal thermometer

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15

**Product**  
 B = Bimetal-thermometer

**1**

**Execution**  
 D = dry  
 W = watertight  
 V = liquid filled

**2**

**Measuring unit**  
 1 = brass  
 2 = stainless steel

**3**

**Case and Bezel, Window**  
 2 = steel black case, aluminum black crimped bezel, synthetic window  
 g = stainless steel case, stainless steel bezel, glass window

**4**

**Mounting**  
 A = bottom  
 C = centerback  
 K = every angle design

**5**

**Case size**  
 3 = 2 1/2"  
 4 = 3 1/4"  
 5 = 4"  
 A = 3"  
 B = 5"

**6**

**Connection**  
 3 = none  
 1 = connection fixed  
 2 = connection turnable  
 K = clamp thermowell  
 S = solder fitting thermowell

**7**

**Thread**  
 0 = none  
 b = 1/2" NPT

**8**

**Size of stem**  
 2 = 1/4"  
 4 = 0.35" / 9 mm

**9**

**Stem length**  
 45 = 1 1/2"  
 63 = 2 1/2"  
 0A = 4"  
 5A = 6"  
 2S = 9"  
 a5 = 12"  
 11 = 15"  
 fh = 18"  
 kg = 24"

**10**  
**11**

**Temperature range**  
 25 - 125°F = 25  
 0 - 140°F = 36  
 32 - 248°F = 51  
 20 - 240°F = 54  
 0 - 250°F = 64  
 50 - 300°F = 71  
 50 - 400°F = 81  
 50 - 500°F = 91  
 150 - 750°F = b2  
 200 - 1000°F = d2

**12**  
**13**

**Temperature scale**  
 3 = °F black  
 6 = °C/°F black  
 8 = °C (red) / °F (black)

**14**

**Options**

**15**

