



# Series 26200



## Remote Nitrogen Filled Thermometers

**Stainless steel case with & bayonet ring with capillary system**  
**Stainless steel stem & connection**  
**Diameter 4" & 6"**

ENFM remote reading nitrogen filled thermometers are designed for precision linear indication of process temperature.

### Execution

- Case:** Stainless steel AISI 304
- Bezel:** Stainless steel AISI 304 bayonet ring
- Dial:** Aluminum, white, with black markings
- Pointer:** Aluminum, black, adjustment screw at back of case
- Window:** Instrument glass
- Connection:** Stainless steel, see table 1
- Stem length:** See table 1
- Stem diameter :** Ø 0.315 ", stainless steel
- Scale:** See table 2, °C/°F
- Capillary length:** See table 3
- Mounting options:** Wall-bracket, Backflange, Frontflange

<b>Series</b>	<b>26201</b>	<b>26201</b>	<b>26221</b>	<b>26221</b>	<b>26234</b>	<b>26234</b>
<b>Case</b>	<b>4"</b>	<b>6"</b>	<b>4"</b>	<b>6"</b>	<b>4"</b>	<b>6"</b>
<b>Stem diameter</b>	<b>0.32"</b>	<b>0.32"</b>	<b>0.32"</b>	<b>0.32"</b>	<b>0.32"</b>	<b>0.32"</b>
<b>Connection</b>	<b>table 1</b>	<b>table 1</b>	<b>table 1</b>	<b>table 1</b>	<b>table 1</b>	<b>table 1</b>
<b>Stem Length</b>	<b>table 1</b>	<b>table 1</b>	<b>table 1</b>	<b>table 1</b>	<b>table 1</b>	<b>table 1</b>
<b>Scale</b>	<b>table 2</b>	<b>table 2</b>	<b>table 2</b>	<b>table 2</b>	<b>table 2</b>	<b>table 2</b>
<b>capillary</b>	<b>table 3</b>	<b>table 3</b>	<b>table 3</b>	<b>table 3</b>	<b>table 3</b>	<b>table 3</b>
<b>Article - number</b>	<b>T32d5</b>	<b>T32d7</b>	<b>T32b5</b>	<b>T32b7</b>	<b>T32f5</b>	<b>T32f7</b>

Table 1	Stem length in inches			
<b>Connection Plain</b>	5" 0032h	7" 0037l	10" 0035o	13" 003d0
<b>Union</b>	min 3.15"			
1/2"NPT	32380			
3/4"NPT	35380			
<b>Sliding Union on stem</b>	min 4"			
1/2"NPT	7230a			
3/4"NPT	7530a			

Table 2	Scale	
Temperature ranges	°F	°F/°C
-75 / 0 / +110 ° F // -60 / 0 / +40 ° C	433	436
-40 / 0 / +140 ° F // -40 / 0 / +60 ° C	453	456
- 4 / 0 / +140 ° F // -20 / 0 / +60 ° C	363	366
-4 / 0 / +175 ° F // -20 / 0 / +80 ° C	473	476
32 / 140 ° F // 0 - 60 ° C	213	216
32 / 175 ° F // 0 - 80 ° C	313	316
32 / 212 ° F // 0 - 100 ° C	413	416
32 / 250 ° F // 0 - 120 ° C	513	516
32 / 320 ° F // 0 - 160 ° C	713	716
32 / 392 ° F // 0 - 200 ° C	813	816
32 / 480 ° F // 0 - 250 ° C	913	916
32 / 575 ° F // 0 - 300 ° C	a13	a16
32 / 750 ° F // 0 - 400 ° C	c13	c16
32 / 930 ° F // 0 - 500 ° C	d13	d16
32 / 1100 ° F // 0 - 600 ° C	e13	e16

Table 3	
capillary length	code
3 feet	1
6 feet	2
9 feet	3
12 feet	4
15 feet	5
18 feet	6
21 feet	7
24 feet	8
27 feet	9
30 feet	a

### Options:

- Other stem diameter.
- Special connections.
- Other stem length.

